Perl Reference Guide Revision 5.001.2
©1989,1996 Johan Vromans.
It may be reproduced, printed and distributed freely for non-profit purposes, as long as the original author gets the credits, and the copyright notice is not removed. It may not be turned into a commercial product except with written permission of the author.
The camel as an image associated with Perl is a trademark of O'Reilly & Associates, Inc. and is used with permission.

Perl Reference Guide

for Perl version 5.001

Perl program designed and created by Larry Wall
<lwall@netlabs.com>

Reference guide designed and created by Johan Vromans
<jvromans@squirrel.nl>

Contents

1. Command line options 2
2. Literals 3
3. Variables 3
4. Operators 4
5. Statements 5
6. Subroutines, packages and modules 5
7. Object oriented programming 6
8. Arithmetic functions 7
9. Conversion functions 7
10. Structure conversion 8
11. String functions 8
12. Array and list functions 9
13. Regular expressions 11
14. Search and replace functions 12
15. File test operators 13
16. File operations 13
17. Input / Output 14
18. Formats 16
19. Directory reading routines 16
20. System interaction 16
21. Networking 18
22. SystemV IPC 18
23. Miscellaneous 19
24. Information from system files 20
25. Special variables 21
26. Special arrays 22
27. Environment variables 22
28. The perl debugger 23

Conventions

fixed	denotes literal text.
THIS	means variable text, i.e. things you must fill in.
THIS†	means that THIS will default to **$_** if omitted.
word	is a keyword, i.e. a word with a special meaning.
RET	denotes pressing a keyboard key.
[…]	denotes an optional part.

1. Command line options

-a turns on autosplit mode when used with **-n** or **-p**. Splits to **@F**.

-c checks syntax but does not execute.

-d runs the script under the debugger. Use '**-de 0**' to start the debugger without a script.

-D NUMBER
sets debugging flags.

-e COMMANDLINE
to enter a single line of script. Multiple **-e** commands may be given to build up a multi-line script.

-F REGEXP
specifies a regular expression to split on if **-a** is in effect.

-i EXT
files processed by the **<>** construct are to be edited in-place.

-I DIR
with **-P**: tells the C preprocessor where to look for include files. The directory is prepended to **@INC**.

-l [OCTNUM]
enables automatic line ending processing, e.g. **-l013**.

-n assumes an input loop around the script. Lines are not printed.

-p assumes an input loop around the script. Lines are printed.

-P runs the C preprocessor on the script before compilation by Perl.

-s interprets '**-xxx**' on the command line as switches and sets the corresponding variables **$xxx** in the script.

-S uses the **PATH** environment variable to search for the script.

-T forces *taint* checking.

-u dumps core after compiling the script. To be used with the *undump* program (where available).

-U allows Perl to perform unsafe operations.

-v prints the version and patchlevel of your Perl executable.

-w prints warnings about possible spelling errors and other error-prone constructs in the script.

-x [DIR]
extracts Perl program from the input stream. If DIR is specified, switches to this directory before running the program.

-0 VAL
(that's the number zero) designates an initial value for the record separator **$/**. See also **-l**.

2. Literals

Numeric: **123 1_234 123.4 5E-10 0xff** (hex) **0377** (octal).

String: **'abc'** literal string, no variable interpolation nor escape characters, except **\'** and ****. Also: **q/abc/**. Almost any pair of delimiters can be used instead of **/**…**/**.

"abc" Variables are interpolated and escape sequences are processed.
Also: **qq/abc/**.
Escape sequences: **\t** (Tab), **\n** (Newline), **\r** (Return), **\f** (Formfeed), **\b** (Backspace), **\a** (Alarm), **\e** (Escape), **\033**(octal), **\x1b**(hex), **\c[** (control).
\l and **\u** lowcase/upcase the following character;
\L and **\U** lowcase/upcase until a **\E** is encountered.
\Q quote regexp characters until a **\E** is encountered.

`COMMAND` evaluates to the output of the COMMAND.
Also: **qx/**COMMAND**/**.

Array: **(1,2,3)**. **()** is an empty array.
(1..4) is the same as **(1,2,3,4)**. Likewise **('abc'..'ade')**.
qw/foo bar …/ is the same as **('foo','bar',…)**.

Array reference: **[1,2,3]**.

Hash (associative array): **(**KEY1, VAL1, KEY2, VAL2, …**)**.
Also: **(**KEY1 **=>** VAL1, KEY2 **=>** VAL2, …**)**.

Hash reference: **{**KEY1, VAL1, KEY2, VAL2, …**}**.

Code reference: **sub {** STATEMENTS **}**

Filehandles: **STDIN**, **STDOUT**, **STDERR**, **ARGV**, **DATA**.
User-specified: HANDLE, **$**VAR.

Globs: **<**PATTERN**>** evaluates to all filenames according to the pattern.
Use '**<${**VAR**}>**' or '**glob $**VAR' to glob from a variable.

Here-Is: **<<**IDENTIFIER *See the Perl manual for details.*

Special tokens:
__FILE__: filename; **__LINE__**: line number.
__END__: end of program; remaining lines can be read using **<**DATA**>**.

3. Variables

$var	a simple scalar variable.
$var[28]	29th element of array **@var**.
$p = \@var	now **$p** is a reference to array **@var**.
$$p[28]	29th element of array referenced by **$p**. Also: **$p->[28]**.
$var[-1]	last element of array **@var**.
$var[$i][$j]	**$j**-th element of **$i**-th element of array **@var**.
$var{'Feb'}	a value from 'hash' (associative array) **%var**.
$p = \%var	now **$p** is a reference to hash **%var**.
$$p{'Feb'}	a value from hash referenced by **$p**. Also: **$p->{'Feb'}**.
$#var	last index of array **@var**.
@var	the entire array; in a scalar context: the number of elements in the array.
@var[3,4,5]	a slice of array **@var**.

`@var{'a','b'}`	a slice of `%var`; same as `($var{'a'},$var{'b'})`.
`%var`	the entire hash; in a scalar context: **true** if the hash has elements.
`$var{'a',1,...}`	emulates a multi-dimensional array.
`('a'..'z')[4,7,9]`	a slice of an array literal.
PKG::VAR	a variable from a package, e.g. `$pkg::var`, `@pkg::ary`.
\OBJECT	reference to an object, e.g. `\$var`, `\%hash`.
*NAME	refers to all objects represented by NAME. '`*n1 = *n2`' makes `n1` an alias for `n2`. '`*n1 = \$n2`' makes `$n1` an alias for `$n2`.

You can always use a `{` BLOCK `}` returning the right type of reference instead of the variable identifier, e.g. `${`…`}`, `&{`…`}`. `$$p` is just a shorthand for `${$p}`.

4. Operators

`**`	Exponentiation.
`+ - * /`	Addition, subtraction, multiplication, division.
`%`	Modulo division.
`& | ^`	Bitwise AND, bitwise OR, bitwise exclusive OR.
`>> <<`	Bitwise shift right, bitwise shift left.
`|| &&`	Logical OR, logical AND.
`.`	Concatenation of two strings.
`x`	Returns a string or array consisting of the left operand (an array or a string) repeated the number of times specified by the right operand.

All of the above operators have an associated assignment operator, e.g. '`.=`'.

`->`	Dereference operator.
`\`	Reference (unary).
`! ~`	Negation (unary), bitwise complement (unary).
`++ --`	Auto-increment (magical on strings), auto-decrement.
`== !=`	Numeric equality, inequality.
`eq ne`	String equality, inequality.
`< >`	Numeric less than, greater than.
`lt gt`	String less than, greater than.
`<= >=`	Numeric less (greater) than or equal to.
`le ge`	String less (greater) than or equal.
`<=> cmp`	Numeric (string) compare. Returns -1, 0 or 1.
`=~ !~`	Search pattern, substitution, or translation (negated).
`..`	Range (scalar context) or enumeration (array context).
`? :`	Alternation (if-then-else) operator.
`,`	Comma operator, also list element separator. You can also use `=>`.
`not`	low-precedence negation.
`and`	low-precedence and.
`or xor`	low-precedence or, xor.

A 'list' is a list of expressions, variables or lists. An array variable or an array slice may always be used instead of a list.
All Perl functions can be used as list operators, in which case they have very high or very low precedence, depending on whether you look at the left side of the operator or at the right side of it. Only the operators **not**, **and**, **or** and **xor**, have lower precedence.
Parentheses can be added around the parameter lists to avoid precedence problems.

5. Statements

Every statement is an expression, optionally followed by a modifier, and terminated with a semicolon. The semicolon may be omitted if the statement is the final one in a BLOCK.

Execution of expressions can depend on other expressions using one of the modifiers **if**, **unless**, **while** or **until**, e.g.:

EXPR1 **if** EXPR2 `;`
EXPR1 **until** EXPR2 `;`

Also, by using one of the logical operators `||`, `&&` or `?:`, e.g.:

EXPR1 `||` EXPR2 `;`
EXPR1 `?` EXPR2 `:` EXPR3 `;`

Statements can be combined to form a BLOCK when enclosed in `{}`. BLOCKs may be used to control flow:

if `(`EXPR`)` BLOCK [[**elsif** `(`EXPR`)` BLOCK ...] **else** BLOCK]
unless `(`EXPR`)` BLOCK [**else** BLOCK]
[LABEL`:`] **while** `(`EXPR`)` BLOCK [**continue** BLOCK]
[LABEL`:`] **until** `(`EXPR`)` BLOCK [**continue** BLOCK]
[LABEL`:`] **for** `(` [EXPR] `;` [EXPR] `;` [EXPR] `)` BLOCK
[LABEL`:`] **foreach** VAR† `(`ARRAY`)` BLOCK
[LABEL`:`] BLOCK [**continue** BLOCK]

Program flow can be controlled with:

goto LABEL
Continue execution at the specified label.

last [LABEL]
Immediately exits the loop in question. Skips continue block.

next [LABEL]
Starts the next iteration of the loop.

redo [LABEL]
Restarts the loop block without evaluating the conditional again.

Special forms are:

do BLOCK **while** EXPR `;`
do BLOCK **until** EXPR `;`

which are guaranteed to perform BLOCK once before testing EXPR, and

do BLOCK

which effectively turns BLOCK into an expression.

6. Subroutines, packages and modules

`&`SUBROUTINE LIST
Executes a SUBROUTINE declared by a **sub** declaration, and returns the value of the last expression evaluated in SUBROUTINE .
SUBROUTINE can be an expression yielding a reference to a code object.
The `&` may be omitted if the subroutine has been declared before being used.

bless REF [`,` PACKAGE]
Turns the object REF into an object in PACKAGE. Returns the reference.

caller [EXPR]
Returns an array (`$`package,`$`file,`$`line,...) for a specific subroutine call.

'**caller**' returns this info for the current subroutine, '**caller(1)**' for the caller of this subroutine etc.. Returns **false** if no caller.

do SUBROUTINE LIST
: Deprecated form of **&**SUBROUTINE .

goto &SUBROUTINE
: Substitutes a call to SUBROUTINE for the current subroutine.

import MODULE [LIST]
: Imports the named subroutines from MODULE.

no MODULE [LIST]
: Cancels imported semantics. See **use**.

package NAME
: Designates the remainder of the current block as a package.

require EXPR†
: If EXPR is numeric, requires Perl to be at least that version. Otherwise EXPR must be the name of a file that is included from the Perl library. Does not include more than once, and yields a fatal error if the file does not evaluate to a **true** value.
If EXPR is a bare word, assumes extension '**.pm**' for the name of the file.

return EXPR
: Returns from a subroutine with the value specified.

sub NAME **{** EXPR **;** … **}**
: Designates NAME as a subroutine. Parameters are passed by reference as array **@_**. Returns the value of the last expression evaluated.

[**sub**] **BEGIN {** EXPR **;** … **}**
: Defines a setup BLOCK to be called before execution.

[**sub**] **END {** EXPR **;** … **}**
: Defines a cleanup BLOCK to be called upon termination.

tie VAR**,** PACKAGE**,** [LIST]
: Ties a variable to a package that will handle it. Can be used to bind a dbm or ndbm file to a hash.

untie VAR
: Breaks the binding between the variable and the package.

use MODULE [LIST]
: Imports semantics from the named module into the current package.

7. Object oriented programming

Perl rules of object oriented programming:

- An object is simply a reference that happens to know which class it belongs to. Objects are blessed, references are not.
- A class is simply a package that happens to provide methods to deal with object references.
  If a package fails to provide a method, the base classes as listed in **@ISA** are searched.
- A method is simply a subroutine that expects an object reference (or a package name, for static methods) as the first argument.
  Methods can be applied with:
  METHOD OBJREF PARAMETERS or
  OBJREF**->**METHOD PARAMETERS

8. Arithmetic functions

abs EXPR†
: Returns the absolute value of its operand.

atan2 Y**,** X
: Returns the arctangent of Y/X in the range -π to π.

cos EXPR†
: Returns the cosine of EXPR (expressed in radians).

exp EXPR†
: Returns **e** to the power of EXPR.

int EXPR†
: Returns the integer portion of EXPR.

log EXPR†
: Returns natural logarithm (base **e**) of EXPR.

rand [EXPR]
: Returns a random fractional number between 0 and the value of EXPR. If EXPR is omitted, returns a value between 0 and 1.

sin EXPR†
: Returns the sine of EXPR (expressed in radians).

sqrt EXPR†
: Returns the square root of EXPR.

srand [EXPR]
: Sets the random number seed for the rand operator.

time
: Returns the number of seconds since January 1, 1970. Suitable for feeding to **gmtime** and **localtime**.

9. Conversion functions

chr EXPR†
: Returns the character represented by the decimal value EXPR.

gmtime EXPR†
: Converts a time as returned by the **time** function to a 9-element array (0:**$**sec, 1:**$**min, 2:**$**hour, 3:**$**mday, 4:**$**mon, 5:**$**year, 6:**$**wday, 7:**$**yday, 8:**$**isdst) with the time analyzed for the Greenwich time zone. **$**mon has the range 0..11 and **$**wday has the range 0..6.

hex EXPR†
: Returns the decimal value of EXPR interpreted as an hex string.

localtime EXPR†
: Converts a time as returned by the **time** function to *ctime*(3) string. In array context, returns a 9-element array with the time analyzed for the local time zone.

oct EXPR†
: Returns the decimal value of EXPR interpreted as an octal string. If EXPR starts off with **0x**, interprets it as a hex string instead.

ord EXPR†
: Returns the ASCII value of the first character of EXPR.

vec EXPR**,** OFFSET**,** BITS
: Treats string EXPR as a vector of unsigned integers, and yields the bit at OFFSET. BITS must be between 1 and 32. May be assigned to.

10. Structure conversion

pack TEMPLATE, LIST
: Packs the values into a binary structure using TEMPLATE.

unpack TEMPLATE, EXPR
: Unpacks the structure EXPR into an array, using TEMPLATE.

TEMPLATE is a sequence of characters as follows:

a / **A**	ASCII string, null / space padded
b / **B**	Bit string in ascending / descending order
c / **C**	Native / unsigned char value
f / **d**	Single / double float in native format
h / **H**	Hex string, low / high nybble first.
i / **I**	Signed / unsigned integer value
l / **L**	Signed / unsigned long value
n / **N**	Short / long in network (big endian) byte order
s / **S**	Signed / unsigned short value
u / **p**	Uuencoded string / Pointer to a string
v / **V**	Short / long in VAX (little endian) byte order
x / **@**	Null byte / null fill until position
X	Backup a byte

Each character may be followed by a decimal number which will be used as a repeat count, '*****' specifies all remaining arguments.
If the format is preceded with %N, **unpack** returns an N-bit checksum instead.
Spaces may be included in the template for readability purposes.

11. String functions

chomp LIST†
: Removes line endings from all elements of the list; returns the (total) number of characters removed.

chop LIST†
: Chops off the last character on all elements of the list; returns the last chopped character.

crypt PLAINTEXT, SALT
: Encrypts a string.

eval EXPR†
: EXPR is parsed and executed as if it were a Perl program. The value returned is the value of the last expression evaluated. If there is a syntax error or runtime error, an undefined string is returned by **eval**, and **$@** is set to the error message. See also **eval** in section 'Miscellaneous'.

index STR, SUBSTR [, OFFSET]
: Returns the position of SUBSTR in STR at or after OFFSET. If the substring is not found, returns **-1** (but see **$[** in section 'Special variables').

length EXPR†
: Returns the length in characters of the value of EXPR.

lc EXPR
: Returns a lower case version of EXPR.

lcfirst EXPR
: Returns EXPR with the first character in lower case.

quotemeta EXPR
: Returns EXPR with all regexp meta-characters quoted.

rindex STR, SUBSTR [, OFFSET]
: Returns the position of the last SUBSTR in STR at or before OFFSET.

substr EXPR, OFFSET [, LEN]
: Extracts a substring out of EXPR and returns it. If OFFSET is negative, counts from the end of the string. May be assigned to.

uc EXPR
: Returns an upper case version of EXPR.

ucfirst EXPR
: Returns EXPR with the first character in upper case.

12. Array and list functions

delete $HASH**{**KEY**}**
: Deletes the specified value from the specified hash. Returns the deleted value unless HASH is **tie**d to a package that does not support it.

each %HASH
: Returns a 2-element array consisting of the key and value for the next value of the hash. Entries are returned in an apparently random order. After all values of the hash have been returned, a null array is returned. The next call to **each** after that will start iterating again.

exists EXPR†
: Checks if the specified hash key exists in its hash array.

grep EXPR, LIST
grep BLOCK LIST
: Evaluates EXPR or BLOCK for each element of the LIST, locally setting **$_** to refer to the element. Modifying **$_** will modify the corresponding element from LIST. Returns the array of elements from LIST for which EXPR returned **true**.

join EXPR, LIST
: Joins the separate strings of LIST into a single string with fields separated by the value of EXPR, and returns the string.

keys %HASH
: Returns an array of all the keys of the named hash.

map EXPR, LIST
map BLOCK LIST
: Evaluates EXPR or BLOCK for each element of the LIST, locally setting **$_** to refer to the element. Modifying **$_** will modify the corresponding element from LIST. Returns the list of results.

pop @ARRAY
: Pops off and returns the last value of the array.

push @ARRAY, LIST
: Pushes the values of LIST onto the end of ARRAY.

reverse LIST
: In array context: returns the LIST in reverse order.
In scalar context: returns the first element of LIST with bytes reversed.

scalar @ARRAY
: Returns the number of elements in the array.

scalar %HASH
: Returns a **true** value if the hash has elements defined.

shift [@ARRAY]
: Shifts the first value of the array off and returns it, shortening the array by 1 and moving everything down. If @ARRAY is omitted, shifts **@ARGV** in main and **@_** in subroutines.

sort [SUBROUTINE] LIST
: Sorts the LIST and returns the sorted array value. If SUBROUTINE is specified, gives the name of a subroutine that returns less than zero, zero, or greater than zero, depending on how the elements of the array, available to the routine as **$a** and **$b**, are to be ordered.
SUBROUTINE may be the name of a user-defined routine, or a BLOCK.

splice @ARRAY, OFFSET [, LENGTH [, LIST]]
: Removes the elements of @ARRAY designated by OFFSET and LENGTH, and replaces them with LIST (if specified).
Returns the elements removed.

split [PATTERN [, EXPR† [, LIMIT]]]
: Splits a string into an array of strings, and returns it. If LIMIT is specified, splits into at most that number of fields. If PATTERN is also omitted, splits on whitespace. If not in array context: returns number of fields and splits to **@_**. See also: 'Search and replace functions'.

unshift @ARRAY, LIST
: Prepends list to the front of the array, and returns the number of elements in the new array.

values %HASH
: Returns a normal array consisting of all the values of the named hash.

13. Regular expressions

Each character matches itself, unless it is one of the special characters **+?.*^$()[]{}|**. The special meaning of these characters can be escaped using a '****'.

. matches an arbitrary character, but not a newline unless it is a single-line match (see **m//s**).

(…**)** groups a series of pattern elements to a single element.

^ matches the beginning of the target. In multi-line mode (see **m//m**) also matches after every newline character.

$ matches the end of the line. In multi-line mode also matches before every newline character.

[…**]** denotes a class of characters to match. **[^**…**]** negates the class.

(…**|**…**|**…**)** matches one of the alternatives.

(?# TEXT **)** Comment.

(?: REGEXP **)** Like **(**REGEXP**)** but does not make back-references.

(?= REGEXP **)** Zero width positive look-ahead assertion.

(?! REGEXP **)** Zero width negative look-ahead assertion.

(? MODIFIER **)** Embedded pattern-match modifier. MODIFIER can be one or more of **i**, **m**, **s** or **x**.

Quantified subpatterns match as many times as possible. When followed with a '**?**' they match the minimum number of times. These are the quantifiers:

+ matches the preceding pattern element one or more times.

? matches zero or one times.

***** matches zero or more times.

{N**,**M**}** denotes the minimum N and maximum M match count. **{**N**}** means exactly N times; **{**N**,}** means at least N times.

A '****' escapes any special meaning of the following character if non-alphanumeric, but it turns most alphanumeric characters into something special:

\w matches alphanumeric, including '**_**', **\W** matches non-alphanumeric.

\s matches whitespace, **\S** matches non-whitespace.

\d matches numeric, **\D** matches non-numeric.

\A matches the beginning of the string, **\Z** matches the end.

\b matches word boundaries, **\B** matches non-boundaries.

\G matches where the previous **m//g** search left off.

\n, **\r**, **\f**, **\t** etc. have their usual meaning.

\w, **\s** and **\d** may be used within character classes, **\b** denotes backspace in this context.

Back-references:

\1…**\9** refer to matched sub-expressions, grouped with **()**, inside the match.

\10 and up can also be used if the pattern matches that many sub-expressions.

See also **$1**…**$9**, **$+**, **$&**, **$`** and **$'** in section 'Special variables'.

With modifier **x**, whitespace can be used in the patterns for readability purposes.

14. Search and replace functions

[EXPR =~] [**m**] /PATTERN/ [**g**] [**i**] [**m**] [**o**] [**s**] [**x**]
: Searches EXPR (default: **$_**) for a pattern. If you prepend an **m** you can use almost any pair of delimiters instead of the slashes. If used in array context, an array is returned consisting of the sub-expressions matched by the parentheses in pattern, i.e. **($1,$2,$3,...)**.
Optional modifiers: **g** matches as many times as possible; **i** searches in a case-insensitive manner; **o** interpolates variables only once.
m treats the string as multiple lines; **s** treats the string as a single line; **x** allows for regular expression extensions.
If PATTERN is empty, the most recent pattern from a previous match or replacement is used.
With **g** the match can be used as an iterator in scalar context.

?PATTERN?
: This is just like the /PATTERN/ search, except that it matches only once between calls to the **reset** operator.

[$VAR =~] s/PATTERN/REPLACEMENT/ [**e**] [**g**] [**i**] [**m**] [**o**] [**s**] [**x**]
: Searches a string for a pattern, and if found, replaces that pattern with the replacement text. It returns the number of substitutions made, if any, otherwise it returns **false**.
Optional modifiers: **g** replaces all occurrences of the pattern; **e** evaluates the replacement string as a Perl expression; for the other modifiers, see /PATTERN/ matching. Almost any delimiter may replace the slashes; if single quotes are used, no interpolation is done on the strings between the delimiters, otherwise they are interpolated as if inside double quotes.
If bracketing delimiters are used, PATTERN and REPLACEMENT may have their own delimiters, e.g. **s(foo)[bar]**.
If PATTERN is empty, the most recent pattern from a previous match or replacement is used.

[$VAR =~] tr/SEARCHLIST/REPLACEMENTLIST/ [**c**] [**d**] [**s**]
: Translates all occurrences of the characters found in the search list with the corresponding character in the replacement list. It returns the number of characters replaced. **y** may be used instead of **tr**.
Optional modifiers: **c** complements the SEARCHLIST; **d** deletes all characters found in SEARCHLIST that do not have a corresponding character in REPLACEMENTLIST; **s** squeezes all sequences of characters that are translated into the same target character into one occurrence of this character.

pos SCALAR
: Returns the position where the last **m//g** search left off for SCALAR. May be assigned to.

study [$VAR†]
: Studies the scalar variable $VAR in anticipation of performing many pattern matches on its contents before the variable is next modified.

15. File test operators

These unary operators take one argument, either a filename or a filehandle, and test the associated file to see if something is true about it. If the argument is omitted, they test **$_** (except for **-t**, which tests **STDIN**). If the special argument **_** (underscore) is passed, they use the info of the preceding test or **stat** call.

-r -w -x	File is readable/writable/executable by effective uid/gid.
-R -W -X	File is readable/writable/executable by real uid/gid.
-o -O	File is owned by effective/real uid.
-e -z	File exists, has zero size.
-s	File exists and has non-zero size. Returns the size.
-f -d	File is a plain file, a directory.
-l -S -p	File is a symbolic link, a socket, a named pipe (FIFO).
-b -c	File is a block/character special file.
-u -g -k	File has setuid/setgid/sticky bit set.
-t	Tests if filehandle (**STDIN** by default) is opened to a tty.
-T -B	File is a text/non-text (binary) file. **-T** and **-B** return **true** on a null file, or a file at EOF when testing a filehandle.
-M -A -C	File modification/access/inode change time. Measured in days. Value returned reflects the file age at the time the script started. See also **$^T** in section 'Special variables'.

16. File operations

Functions operating on a list of files return the number of files successfully operated upon.

chmod LIST
: Changes the permissions of a list of files. The first element of the list must be the numerical mode.

chown LIST
: Changes the owner and group of a list of files. The first two elements of the list must be the numerical uid and gid.

truncate FILE, SIZE
: truncates FILE to SIZE. FILE may be a filename or a filehandle.

link OLDFILE, NEWFILE
: Creates a new filename linked to the old filename.

lstat FILE
: Like stat, but does not traverse a final symbolic link.

mkdir DIR, MODE
: Creates a directory with given permissions. Sets **$!** on failure.

readlink EXPR†
: Returns the value of a symbolic link.

rename OLDNAME, NEWNAME
: Changes the name of a file.

rmdir FILENAME†
: Deletes the directory if it is empty. Sets **$!** on failure.

stat FILE
: Returns a 13-element array (0:**$**dev, 1:**$**ino, 2:**$**mode, 3:**$**nlink, 4:**$**uid, 5:**$**gid, 6:**$**rdev, 7:**$**size, 8:**$**atime, 9:**$**mtime, 10:**$**ctime, 11:**$**blksize, 12:**$**blocks). FILE can be a filehandle, an expression evaluating to a filename, or **_** to refer to the last file test operation or **stat** call. Returns a null list if the **stat** fails.

symlink OLDFILE, NEWFILE
: Creates a new filename symbolically linked to the old filename.

unlink LIST
: Deletes a list of files.

utime LIST
: Changes the access and modification times. The first two elements of the list must be the numerical access and modification times.

17. Input / Output

In input/output operations, FILEHANDLE may be a filehandle as opened by the **open** operator, a pre-defined filehandle (e.g. **STDOUT**) or a scalar variable which evaluates to the name of a filehandle to be used.

<FILEHANDLE**>**
: In scalar context: reads a single line from the file opened on FILEHANDLE. In array context: reads the whole file.

< > Reads from the input stream formed by the files specified in **@ARGV**, or standard input if no arguments were supplied.

binmode FILEHANDLE
: Arranges for the file opened on FILEHANDLE to be read or written in *binary* mode as opposed to *text* mode (null-operation on UNIX).

close FILEHANDLE
: Closes the file or pipe associated with the file handle.

dbmclose %HASH
: Deprecated, use **untie** instead.

dbmopen %HASH, DBMNAME, MODE
: Deprecated, use **tie** instead.

eof FILEHANDLE
: Returns 1 if the next read will return end of file, or if the file is not open.

eof Returns the eof status for the last file read.

eof( ) Indicates eof on the pseudo-file formed of the files listed on the command line.

fcntl FILEHANDLE, FUNCTION, **$**VAR
: Implements the *fcntl*(2) function. This function has non-standard return values. See the manual for details.

fileno FILEHANDLE
: Returns the file descriptor for a given (open) file.

flock FILEHANDLE, OPERATION
: Calls *flock*(2) on the file. OPERATION formed by adding 1 (shared), 2 (exclusive), 4 (non-blocking) or 8 (unlock).

getc [FILEHANDLE]
: Yields the next character from the file, or **""** on end of file. If FILEHANDLE is omitted, reads from **STDIN**.

ioctl FILEHANDLE, FUNCTION, **$**VAR
: performs *ioctl*(2) on the file. This function has non-standard return values. See the manual for details.

open FILEHANDLE [, FILENAME]
: Opens a file and associates it with FILEHANDLE. If FILENAME is omitted, the scalar variable of the same name as the FILEHANDLE must contain the filename.

  The following filename conventions apply when opening a file.

  "FILE**"** open FILE for input. Also **"<**FILE**"**.

  ">FILE**"** open FILE for output, creating it if necessary.

  ">>FILE**"** open FILE in append mode.

  "+<FILE**"** open FILE with read/write access.

  "|CMD**"** opens a pipe to command CMD. If CMD is '**–**', forks.

  "CMD**|"** opens a pipe from command CMD. If CMD is '**–**', forks.

  FILE may be **&**FILEHND, in which case the new file handle is connected to the (previously opened) filehandle FILEHND. If it is **&=**N, FILE will be connected to the given file descriptor.

  open returns **undef** upon failure, **true** otherwise.

pipe READHANDLE, WRITEHANDLE
: Returns a pair of connected pipes.

print [FILEHANDLE] [LIST†]
: Prints the elements of LIST, converting them to strings if needed. If FILEHANDLE is omitted, prints by default to standard output (or to the last selected output channel, see **select**).

printf [FILEHANDLE] LIST]
: Equivalent to **print** FILEHANDLE **sprintf** LIST.

read FILEHANDLE, **$**VAR, LENGTH [, OFFSET]
: Reads LENGTH binary bytes from the file into the variable at OFFSET. Returns number of bytes actually read.

seek FILEHANDLE, POSITION, WHENCE
: Arbitrarily positions the file. Returns 1 upon success, 0 otherwise.

select [FILEHANDLE]
: Returns the currently selected filehandle. Sets the current default filehandle for output operations if FILEHANDLE is supplied.

select RBITS, WBITS, NBITS, TIMEOUT
: Performs a *select*(2) system call with the same parameters.

sprintf FORMAT, LIST
: Returns a string formatted by (almost all of) the usual *printf*(3) conventions.

sysread FILEHANDLE, **$**VAR, LENGTH [, OFFSET]
: Reads LENGTH bytes into **$**VAR at OFFSET.

syswrite FILEHANDLE, SCALAR, LENGTH [, OFFSET]
: Writes LENGTH bytes from SCALAR at OFFSET.

tell [FILEHANDLE]
: Returns the current file position for the file. If FILEHANDLE is omitted, assumes the file last read.

18. Formats

formline PICTURE, LIST
: Formats LIST according to PICTURE and accumulates the result into **$^A**.

write [FILEHANDLE]
: Writes a formatted record to the specified file, using the format associated with that file.

Formats are defined as follows:

format [NAME] **=**
FORMLIST
.

FORMLIST pictures the lines, and contains the arguments which will give values to the fields in the lines. NAME defaults to **STDOUT** if omitted.
Picture fields are:

@<<<…	left adjusted field, repeat the **<** to denote the desired width;
@>>>…	right adjusted field;
@|||…	centered field;
@#.##…	numeric format with implied decimal point;
@*	a multi-line field.

Use **^** instead of **@** for multi-line block filling.

Use **~** at the beginning of a line to suppress unwanted empty lines.

Use **~~** at the beginning of a line to have this format line repeated until all fields are exhausted.

Set **$-** to zero to force a page break.

See also **$^**, **$~**, **$^A**, **$^F**, **$-** and **$=** in section 'Special variables'.

19. Directory reading routines

closedir DIRHANDLE
: Closes a directory opened by opendir.

opendir DIRHANDLE, DIRNAME
: Opens a directory on the handle specified.

readdir DIRHANDLE
: Returns the next entry (or an array of entries) in the directory.

rewinddir DIRHANDLE
: Positions the directory to the beginning.

seekdir DIRHANDLE, POS
: Sets position for readdir on the directory.

telldir DIRHANDLE
: Returns the postion in the directory.

20. System interaction

alarm EXPR
: Schedules a **SIGALRM** to be delivered after EXPR seconds.

chdir [EXPR]
: Changes the working directory.
Uses **$ENV{"HOME"}** or **$ENV{"LOGNAME"}** if EXPR is omitted.

chroot FILENAME†
: Changes the root directory for the process and its children.

die [LIST]
: Prints the value of LIST to **STDERR** and exits with the current value of **$!** (errno). If **$!** is 0, exits with the value of **($? >> 8)**. If **($? >> 8)** is 0, exits with 255. LIST defaults to **"Died"**.

exec LIST
: Executes the system command in LIST; does not return.

exit [EXPR]
: Exits immediately with the value of **EXPR**, which defaults to **0** (zero). Calls **END** routines and object destructors before exiting.

fork Does a *fork*(2) system call. Returns the child pid to the parent process and zero to the child process.

getlogin
: Returns the current login name as known by the system.

getpgrp [PID]
: Returns the process group for process PID (0, or omitted, means the current process).

getppid
: Returns the process id of the parent process.

getpriority WHICH, WHO
: Returns the current priority for a process, process group, or user.

glob PAT
: Returns a list of filenames that match the shell pattern PAT.

kill LIST
: Sends a signal to a list of processes. The first element of the list must be the signal to send (numeric, or its name as a string).

setpgrp PID, PGRP
: Sets the process group for the PID (0 = current process).

setpriority WHICH, WHO, PRIO
: Sets the current priority for a process, process group, or a user.

sleep [EXPR]
: Causes the script to sleep for EXPR seconds, or forever if no EXPR. Returns the number of seconds actually slept.

syscall LIST
: Calls the system call specified in the first element of the list, passing the rest of the list as arguments to the call.

system LIST
: Does exactly the same thing as **exec** LIST except that a fork is performed first, and the parent process waits for the child process to complete.

times
: Returns a 4-element array (0:**$**user, 1:**$**system, 2:**$**cuser, 3:**$**csystem) giving the user and system times, in seconds, for this process and the children of this process.

umask [EXPR]
: Sets the umask for the process and returns the old one. If EXPR is omitted, returns current umask value.

wait Waits for a child process to terminate and returns the pid of the deceased process (-1 if none). The status is returned in **$?**.

waitpid PID, FLAGS
Performs the same function as the corresponding system call.

warn [LIST]
Prints the message on **STDERR** like **die**, but does not exit.
LIST defaults to **"Warning: something's wrong"**.

21. Networking

accept NEWSOCKET, GENERICSOCKET
Accepts a new socket.

bind SOCKET, NAME
Binds the NAME to the SOCKET.

connect SOCKET, NAME
Connects the NAME to the SOCKET.

getpeername SOCKET
Returns the socket address of the other end of the SOCKET.

getsockname SOCKET
Returns the name of the socket.

getsockopt SOCKET, LEVEL, OPTNAME
Returns the socket options.

listen SOCKET, QUEUESIZE
Starts listening on the specified SOCKET.

recv SOCKET, SCALAR, LENGTH, FLAGS
Receives a message on SOCKET.

send SOCKET, MSG, FLAGS [, TO]
Sends a message on the SOCKET.

setsockopt SOCKET, LEVEL, OPTNAME, OPTVAL
Sets the requested socket option.

shutdown SOCKET, HOW
Shuts down a SOCKET.

socket SOCKET, DOMAIN, TYPE, PROTOCOL
Creates a SOCKET in DOMAIN with TYPE and PROTOCOL.

socketpair SOCKET1, SOCKET2, DOMAIN, TYPE, PROTOCOL
As socket, but creates a pair of bi-directional sockets.

22. SystemV IPC

msgctl ID, CMD, ARGS
Calls *msgctl*(2). If CMD is **&IPC_STAT** then ARG must be a variable.

msgget KEY, FLAGS
Creates a message queue for KEY. Returns the message queue identifier.

msgsnd ID, MSG, FLAGS
Sends MSG to queue ID.

msgrcv ID, **$**VAR, SIZE, TYPE, FLAGS
Receives a message from queue ID into VAR.

semctl ID, SEMNUM, CMD, ARG
Calls *semctl*(2).
If CMD is **&IPC_STAT** of **&GETALL** then ARG must be a variable.

semget KEY, NSEMS, SIZE, FLAGS
Creates a set of semaphores for KEY. Returns the message semaphore identifier.

semop KEY, ...
Performs semaphore operations.

shmctl ID, CMD, ARG
Calls *shmctl*(2). If CMD is **&IPC_STAT** then ARG must be a variable.

shmget KEY, SIZE, FLAGS
Creates shared memory. Returns the shared memory segment identifier.

shmread ID, **$**VAR, POS, SIZE
Reads at most SIZE bytes of the contents of shared memory segment ID starting at offset POS into VAR.

shmwrite ID, STRING, POS, SIZE
Writes at most SIZE bytes of STRING into the contents of shared memory segment ID at offset POS.

23. Miscellaneous

defined EXPR
Tests whether the lvalue EXPR has an actual value.

do FILENAME
Executes FILENAME as a Perl script. See also **require** in section 'Subroutines, packages and modules'.

dump [LABEL]
Immediate core dump. When reincarnated, starts at LABEL.

eval {EXPR**; …}**
Executes the code between **{** and **}**. Traps run-time errors as described with **eval(**EXPR**)**, section 'String functions'.

local LIST
Creates a scope for the listed variables local to the enclosing block, subroutine or eval.

my LIST
Creates a scope for the listed variables lexically local to the enclosing block, subroutine or eval.

ref EXPR†
Returns a **true** value if EXPR is a reference. Returns the package name if EXPR has been blessed into a package.

reset [EXPR]
Resets **??** searches so that they work again. EXPR is a list of single letters. All variables and arrays beginning with one of those letters are reset to their pristine state. Only affects the current package.

scalar EXPR
Forces evaluation of EXPR in scalar context.

undef [LVALUE]
Undefines the LVALUE. Always returns the undefined value.

wantarray
Returns **true** if the current context expects an array value.

24. Information from system files

See the manual about return values in scalar context.

passwd

Returns (**$**name, **$**passwd, **$**uid, **$**gid, **$**quota, **$**comment, **$**gcos, **$**dir, **$**shell).

endpwent	Ends look-up processing.
getpwent	Gets next user information.
getpwnam NAME	Gets information by name.
getpwuid UID	Gets information by user ID.
setpwent	Resets look-up processing.

group

Returns (**$**name, **$**passwd, **$**gid, **$**members).

endgrent	Ends look-up processing.
getgrgid GID	Gets information by group ID.
getgrnam NAME	Gets information by name.
getgrent	Gets next group information.
setgrent	Resets look-up processing.

hosts

Returns (**$**name, **$**aliases, **$**addrtype, **$**length, @addrs).

endhostent	Ends look-up processing.
gethostbyaddr ADDR, ADDRTYPE	Gets information by IP address.
gethostbyname NAME	Gets information by host name.
gethostent	Gets next host information.
sethostent STAYOPEN	Resets look-up processing.

networks

Returns (**$**name, **$**aliases, **$**addrtype, **$**net).

endnetent	Ends look-up processing.
getnetbyaddr ADDR, TYPE	Gets information by address and type.
getnetbyname NAME	Gets information by network name.
getnetent	Gets next network information.
setnetent STAYOPEN	Resets look-up processing.

services

Returns (**$**name, **$**aliases, **$**port, **$**proto).

endservent	Ends look-up processing.
getservbyname NAME, PROTO	Gets information by service name.
getservbyport PORT, PROTO	Gets information by service port.
getservent	Gets next service information.
setservent STAYOPEN	Resets look-up processing.

protocols

Returns (**$**name, **$**aliases, **$**proto).

endprotoent	Ends look-up processing.
getprotobyname NAME	Gets information by protocol name.
getprotobynumber NUMBER	Gets information by protocol number.
getprotoent	Gets next protocol information.
setprotoent STAYOPEN	Resets look-up processing.

25. Special variables

The following variables are global and should be localized in subroutines:

$_	The default input and pattern-searching space.
$.	The current input line number of the last filehandle that was read.
$/	The input record separator, newline by default. May be multi-character.
$,	The output field separator for the print operator.
$"	The separator which joins elements of arrays interpolated in strings.
$	The output record separator for the print operator.
$#	The output format for printed numbers. Deprecated.
$*	Set to 1 to do multiline matching within strings. Deprecated, see the **m** and **s** modifiers in section 'Search and replace functions'.
$?	The status returned by the last `...` command, pipe **close** or **system** operator.
$]	The Perl version number, e.g. **5.001**.
$[	The index of the first element in an array, and of the first character in a substring. Default is 0. Deprecated.
$;	The subscript separator for multi-dimensional array emulation. Default is **"\034"**.
$!	If used in a numeric context, yields the current value of **errno**. If used in a string context, yields the corresponding error string.
$@	The Perl error message from the last **eval** or **do** EXPR command.
$:	The set of characters after which a string may be broken to fill continuation fields (starting with '^') in a format.
$0	The name of the file containing the Perl script being executed. May be assigned to.
$$	The process number of the Perl interpreter running this script. Altered (in the child process) by **fork**.
$<	The real user ID of this process.
$>	The effective user ID of this process.
$(	The real group ID of this process.
$)	The effective group ID of this process.
$^A	The accumulator for **formline** and **write** operations.
$^D	The debug flags as passed to Perl using '**-D**'.
$^F	The highest system file descriptor, ordinarily 2.
$^I	In-place edit extension as passed to Perl using '**-i**'.
$^L	Formfeed character used in formats.
$^P	Internal debugging flag.
$^T	The time (as delivered by **time**) when the program started. This value is used by the file test operators '**-M**', '**-A**' and '**-C**'.
$^W	The value of the '**-w**' option as passed to Perl.
$^X	The name by which this Perl interpreter was invoked.

The following variables are context dependent and need not be localized:

$%	The current page number of the currently selected output channel.
$=	The page length of the current output channel. Default is 60 lines.
$-	The number of lines remaining on the page.
$~	The name of the current report format.

$^ The name of the current top-of-page format.

$| If set to nonzero, forces a flush after every write or print on the output channel currently selected. Default is 0.

$ARGV The name of the current file when reading from **<>** .

The following variables are always local to the current block:

$& The string matched by the last successful pattern match.

$` The string preceding what was matched by the last successful match.

$' The string following what was matched by the last successful match.

$+ The last bracket matched by the last search pattern.

$1…**$9**… Contain the subpatterns from the corresponding sets of parentheses in the last pattern successfully matched. **$10**…and up are only available if the match contained that many subpatterns.

26. Special arrays

@ARGV Contains the command line arguments for the script (not including the command name).

@EXPORT
Names the methods a package exports by default.

@EXPORT_OK
Names the methods a package can export upon explicit request.

@INC Contains the list of places to look for Perl scripts to be evaluated by the **do** FILENAME and **require** commands.

@ISA List of *base classes* of a package.

@_ Parameter array for subroutines. Also used by **split** if not in array context.

%ENV Contains the current environment.

%INC List of files that have been included with **require** or **do**.

%OVERLOAD
Can be used to overload operators in a package.

%SIG Used to set signal handlers for various signals.

27. Environment variables

Perl uses the following environment variables.

HOME Used if **chdir** has no argument.

LOGDIR
Used if **chdir** has no argument and **HOME** is not set.

PATH Used in executing subprocesses, and in finding the Perl script if '**-S**' is used.

PERL5LIB
A colon-separated list of directories to look in for Perl library files before looking in the standard library and the current directory.

PERL5DB
The command to get the debugger code.
Defaults to **BEGIN { require 'perl5db.pl' }**.

PERLLIB
Used instead of **PERL5LIB** if the latter is not defined.

Perl Reference Guide Revision 5.001.2
©1989,1996 Johan Vromans.
It may be reproduced, printed and distributed freely for non-profit purposes, as long as the original author gets the credits, and the copyright notice is not removed. It may not be turned into a commercial product except with written permission of the author.
The camel as an image associated with Perl is a trademark of O'Reilly & Associates, Inc. and is used with permission.